

## Filter Pump Specification

Item#	Model #	Pump Flow	Standard working	Power Cord	Voltage	Amps	Watts	HP (Approx.)	IP Code	Replace Cartridge/Sand with
		US Gal.	Bar (Psi)	ft (m)						
28601/EG	601	330 (1,250)	0.15 (2.18)	25 (7.62)	110-120V ac / 60Hz	0.42	30			29007
28602	602	330 (1,250)	0.15 (2.18)	10 (3.00)	220-240V ac / 50Hz	0.15	30	3/64	IPX5/IPX7	29007
28603/EG	603	530 (2,006)	0.15 (2.18)	25 (7.62)	110-120V ac / 60Hz	0.7	45			59900/29000
28604	604	530 (2,006)	0.15 (2.18)	10 (3.00)	220-240V ac / 50Hz	0.3	45	1/16	IPX5/IPX7	59900/29000
28637/EG	637R	1,000 (3,785)	0.18 (2.60)	25 (7.62)	110-120V ac / 60Hz	1.4	99			59900/29000
28638	638R	1,000 (3,785)	0.18 (2.60)	10 (3.00)	220-240V ac / 50Hz	0.5	99	1/8	IPX5/IPX7	59900/29000
28635/EG	635T	1,500 (5,678)	0.20 (2.90)	25 (7.62)	110-120V ac / 60Hz	2.1	155			59900/29000
28636	636T	1,500 (5,678)	0.20 (2.90)	10 (3.00)	220-240V ac / 50Hz	1.0	165	1/5	IPX5	59900/29000
28633/EG	633T	2,500 (9,462)	0.70 (10.20)	25 (7.62)	110-120V ac / 60Hz	3.3	360			59905/29005
28634	634T	2,500 (9,462)	0.70 (10.20)	10 (3.00)	220-240V ac / 50Hz	1.7	360	1/2	IPX4	59905/29005
56621	FP621R	4,000 (15,140)	1.10 (16.00)	25 (7.62)	110-120V ac / 60Hz	6.0	650			59905/29005
56622	FP622R	4,000 (15,140)	1.10 (16.00)	10 (3.00)	220-240V ac / 50Hz	3.0	650	3/4	IPX4	59905/29005
28602GS	602G	330 (1,250)	0.12 (1.75)	18 (5.50)	Input: 220-240V ac / 50Hz  Output: 12V ac	3.0	30	3/64	IPX7	29007
28604GS	604G	600 (2,271)	0.12 (1.75)	18 (5.50)		5.0	55	1/12	IPX7	59900/29000
28638GS	638G	900 (3,406)	0.16 (2.32)	18 (5.50)		8.0	90	1/8	IPX7	59900/29000
28636GS	636G	1,500 (5,678)	0.20 (2.90)	18 (5.50)		15.0	160	1/4	IPX5	59900/29000
28634GS	634RC	2,500 (9,462)	0.70 (10.20)	10 (3.00)	220-240V ac / 50Hz	1.8	190	1/4	IPX4	59905/29005

**\*Note:** Models with "T" suffix include a built-in timer feature.